



AT4275EC

28" Clamping Tire Changer



The AT4275EC, swing arm tire changer is perfect for the medium volume service shop. This changer is rigid, reliable and fast!

The AT4275EC is capable of safely and efficiently handling virtually any wheel combination for passenger, SUV, performance & light truck vehicles.

KEY FEATURES

- Hand Operated Bead breaker
- G frame structure to reduce flex.
- 2 speed rotation gives control over the mounting process.
- Independent helper arms for flexibility when mounting difficult wheels.
- Clamping range 12" to 28"
- 2 Year parts AND labor warranty!

For more information, please contact:

BASE
USA

Toll Free # 855-BASE-113 or at www.baseusa.com

AT4275 - Features/User Benefits



ERGO CONTROL BEAD BREAKER

User Benefits:

- Fast with Less Effort
- No shock on the Operators Arm!
- Full Proportional Control; you control the movement of the shovel.
- Intuitive, Easy to use: your fingers make the shovel move.
- 2 working ranges
- Bead breaking Force: 11500N.



SIDE LIFT - (OPTIONAL #1695107466)

User Benefits:

- Fast & Simple to use.
- Ergonomic design eliminates back stress.
- Freedom for the feet: lift stays up, even when the operator steps away.
- Saves time: not necessary to move the wheel after the bead breaking operations.
- Creates greater productivity.
- Roller board integrated.



STANDARD ACCESSORIES- AT 4275



Lubricant brush (x1)



Bead lever (x1)



Mount/Demount head protectors (5pcs.)



Wing side protection for demounting head (x1)



Bead breaker plastic protection (x1)



Bead pressing device (x1)



Plastic Jaw protection kit(4pcs.)

TECHNICAL SPECIFICATIONS - AT4275

Power supply:	110V - 1ph - 50/60Hz or Air Motor
Air supply pressure:	116-145 Psi
Rim diameter:	12"-28"
Max. Wheel diameter:	47"
Max Rim width:	15"
Turntable speed:	2 speed motor
Rotation speed:	7 & 15 RPM
Breaker range:	up to 15" - Ergo Control
Breaking force:	11500 N



1314 Centerview Circle
Copley, OH 44321
Toll Free: 1-855-227-3113
www.baseusa.com