



AT4295

32" Center Clamping Tire Changer



Accu-turn introduces a new innovative, high volume service, tire changer which combines the familiarity of a traditional swing arm and the versatility of a modern center post!

The AT4295 is capable of safely and efficiently handling virtually any wheel combination for both passenger and light truck vehicles.

Key Features

- Center post clamping with a faster & easier locking system.
- Ergo bead breaker - operator has control!
- 2 speed rotation gives control over the mounting process.
- 2 independent helpers for flexibility when clamping difficult wheels.
- Clamping range up to 32"
- 2 Year parts AND labor warranty!

For more information, please contact:

BASE
USA

Toll Free # 855-BASE-113 or at www.baseusa.com

AT4295 - Features/User Benefits

CONVIENENT

- control switch follows you

2 SEPERATE HELPERS

- provides greater flexibility

FAST & ROBUST

- center post locking system

EASY ACCESS

- tool holder

FAST

- pedal controlled, two speed turntable

SIMPLE

- single pedal design



SPACE SAVER

- Swing arm solution

POLE TANK

- more air volume for tire inflation

ADJUSTABLE BEAD BREAKER

- breaks down wider range of tires

ERGO CONTROL

- operator controls bead breaking process

STORAGE

- for tools, valves...

STANDARD ACCESSORIES- AT 4295



Lube Brush (x1)



Mount/Demount head protectors (5 pcs.)



Wing side protection for demounting head (x1)



Bead breaker plastic protection (x1)



Centre locking protection (x2)



Bead Lever (x1)



Cone protection tool locking system (x2)



Pin protection locking system (x2)



Cone Ø 70 mm (x1)



Bead pressing device (x1)

TECHNICAL SPECIFICATIONS - AT4295

Power supply:	110V - 1ph - 50/60Hz/20 amp or Air
Air supply pressure:	Motor 116-145 Psi
Rim diameter:	12" - 32"
Max. Wheel diameter:	47"
Max Rim width:	15"
Turntable:	2 speed motor
Rotation speed:	7 & 15 RPM
Bead breaker range:	up to 15" - Ergo Control
Bead breaking force:	11500 N



1314 Centerview Circle
Copley, OH 44321

Toll Free: 855-227-3113
www.baseusa.com