



AT4475EC

28" Clamping Tire Changer

A professional line tire changer, designed for the high volume shop. Its wide clamping range, hand bead breaker and 2 speed rotation make the AT4475EC versatile, safe and fast!

The AT4475EC, with its independent arm and helper, is capable of safely and efficiently handling virtually any wheel combination for passenger, SUV, performance and light truck vehicles.

KEY FEATURES

- Fast and Robust for High volume work shops
- Tilt back design
- Rigid G Frame structure
- Ergo Bead Breaker
- Single button locking for automatic positioning of M/D head.
- 2 Speed rotation giving more control over the mounting process.
- Clamping range 12" - 28"
- Optional Tire lift available (pn#1695107466)
- 2 years parts AND labor warranty!



For more information, please contact:

BASE
USA

Toll Free # 855-BASE-113 or at www.baseusa.com

AT 4475EC-Features/User Benefits

EASY ACCESS

- Control switches follow you

PUSH & LOCK

- Pneumatic positioning and locking of the mounting heads

SEPERATE HELPERS

- Smooth & powerful motion

ADAPTABLE

- Clamping 28 to 32"
Wheel width up to 15"

VERSITILE

- Steel rims=internal clamping
alloy rims=protected external clamping

ERGO CONTROL

- Not just an ordinary bead breaker! Easy to use, more control means less rim damage.



Helper Arm

- Assists during mounting and demounting operation, especially with UHP and RFT tires.
- Separate movements of tools
 - precise control
 - press and/or release where needed
- Control switches ergonomically positioned
- Horizontal arm mounted close to mounting head
- Locking system to hold the horizontal arm in position when used.
- Space saving, small footprint



STANDARD ACCESSORIES – AT4475



Lubricant brush (x1)



Bead lever (x1)



Plastic Jaw protector set (4pcs.)



Mount/Demount head protectors (5pcs.)



Wing side protection for demounting head (x1)



Bead breaker plastic protection (x1)



Bead pressing device (x1)

TECHNICAL SPECIFICATIONS- AT4475

Power supply:	110V 1ph 50/60Hz/20 amp or Air motor
Air supply pressure:	110-145 PSI
Rim diameter:	12" - 28"
Max. Wheel diameter:	47"
Max Rim width:	Up to 15"
Turntable:	2 speed motor
Rotation speed:	7 - 15 RPM
Bead breaker range:	16" - Ergo control
Bead breaking force:	11500 N



1314 Centerview Circle
Copley, OH 44321

Toll Free: 855-227-3113
www.baseusa.com